



CB5 Series

Carbon Block Replacement Cartridges

CB5 Family of Carbon Block Water Filter Cartridges

Premium Quality Water for Foodservice Applications in Problem Water Areas

BENEFITS

- Reduces chlorine and other off tastes and odors.
- Carbon block technology removes dirt and particles down to five microns in size.
- Removes moldy and earthy tastes, which adversely affect the appeal of ice, cold and hot beverages.
- The 2CB5-S, 4CB5-S and 7CB5-S also reduce limescale buildup that can cause excessive machine downtime, and helps reduce maintenance costs.
- The 2CB5-K, 4CB5-K, and 7CB5-K feature KDF® media which prevents microbial buildup and provides scale inhibition for water-using equipment.



Capacity: 3,000 gallons (11,355 L)
 Flow rate : 1 gpm (3.8 Lpm)
 Available Models:
 2CB5 (9617-05;6 Pack)
 2CB5-S (9617-22;6 Pack)
 2CB5-K (9617-06;6 Pack)



Capacity:6,000 gallons (22,710 L)
 Flow rate: 1.67 gpm (6.3 Lpm)
 Available Models:
 4CB5 (9617-16;6 Pack)
 4CB5-S (9617-26;6 Pack)
 4CB5-K (9617-36;6 Pack)



Capacity:10,000 gallons (37,850 L)
 Flow rate: 2.5 gpm (9.5 Lpm)
 Available Models:
 7CB5 (9618-16; 6 Pack)
 7CB5-S (9618-26; 6 Pack)
 7CB5-K (9617-76; 6 Pack)

INSTALLATION AND OPERATION TIPS

- When installing, allow 2-1/2" clearance below cartridge for cartridge replacement.
- Do not exceed recommended service flow rate.
- Flush filter cartridge by running water through cartridge for several minutes to purge air and possible carbon fines.
- Change cartridges on a regular 6 month preventative maintenance basis.

Product Features:	CB5	CB5-S	CB5-K
Chlorine Reduction	✓	✓	✓
Off Tastes & Odor Reduction	✓	✓	✓
Particulate Reduction	✓	✓	✓
Limescale Reduction		✓	✓
Microbial Buildup Reduction			✓

2CB5/S/K

Specifications

Dimensions: 10.75" x 3.125"

Service Flow Rate: 1.0 gpm (3.8 Lpm)

Pressure: Min.10 psi

Max.125 psi (nonshock)

Max. Temperature:100°F (38°C)

No Electrical Connection Required

Shipping Weight:9 lbs. (6 pack)

4CB5/S/K

Specifications

Dimensions: 14.75" x 3.125"

Service Flow Rate:1.67 gpm (6.3 Lpm)

Pressure: Min.10 psi

Max. 125 psi (nonshock)

Max. Temperature: 100°F (38°C)

No Electrical Connection Required

Shipping Weight:13 lbs. (6 pack)



7CB5/S/K

Specifications

Dimensions:20.75" x 3.125"

Service Flow Rate: 2.5 gpm (9.5 Lpm)

Pressure: Min.10 psi

Max.125 psi (nonshock)

Max. Temperature: 100°F (38°C)

No Electrical Connection Required

Shipping Weight:19 lbs. (6 pack)

LIMITED WARRANTY OF PHYSICAL QUALITY

If, within eighteen months after manufacture or twelve months after purchase (whichever occurs first), any part of Everpure, Inc.manufacture which is returned to its factory, shipping charges prepaid, is found to be defective in material or workmanship in the judgement of Everpure's engineers, Everpure, Inc.will repair or replace such part at no charge, f.o.b., Westmont factory. Everpure, Inc.however, shall not be liable for damages or delays caused by any defective material or workmanship, or by failure of any parts due to normal wear and tear. Everpure, Inc.will not be responsible for products which malfunction due to user neglect or unauthorized modification.

NOTE:Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.Similarly, some states do not allow the exclusion or limitation of consequential or incidental damages, so the above limitation or exclusion may not apply to you.This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.



The 2CB5, 2CB5-K, 2CB5-S, 4CB5, 4CB5-K, 4CB5-S, 7CB5, 7CB5-K & 7CB5-S filter cartridges have been tested and listed by NSF only for the functions listed above. Check for compliance with state and local laws and regulations. Do not use where the water is microbiologically unsafe, or with waters of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

EVERPURE
WATER YOU CAN TRUST.

EVERPURE, INC.

660 Blackhawk Drive
Westmont, IL 60559-9005
Tel (630) 654-4000
FAX (630) 654-1115
Technical Service
(800) 942-1153
<http://www.everpure.com>

N.V. EVERPURE (EUROPE) S.A.

Research Park, Haasrode
B-3001 Heverlee
Belgium
Tel 32-16-401191
FAX 32-16-402691

EVERPURE JAPAN, INC.

1-8-19, Tsumada Kita,
Atsugi-Shi
Kanagawa 243
Japan
Tel 81-462 (23) 6563
FAX 81-462 (21) 6775